

PLS6.150D With SuperSpeed™

Speed and Flexibility

The PLS6.150D with SuperSpeed™ (PLS6.150DSS) platform is designed and engineered for demanding applications requiring maximum productivity. The PLS6.150DSS platform offers a truly flexible solution through its modular design. Lasers, focusing optics and many other modules can easily be added or removed to reconfigure the laser system to meet specific material or application requirements. Interchangeable factory pre-aligned laser sources can be individually or simultaneously controlled, producing a broad range of power, from 10 to 150 W.



SuperSpeed™ Technology

This patented technology uses a dual-laser configuration, pulsing the beams independently, making it possible for two lines of a raster image to be engraved or marked simultaneously. This enables the PLS6.150DSS to perform laser marking and engraving in literally half the time, making the PLS6.150DSS the fastest laser system in the world. For vector cutting, the laser beams can be combined to take advantage of higher power.

Laser Technology Benefits

- ▶ **Software Controlled** - Any Windows®-based software with a print function can be used with the laser system.
- ▶ **Multi-Material** - Process an endless number of materials.
- ▶ **Multi-Process** - Cut, engrave, mark and produce photo images in one step.
- ▶ **Non-Contact** - Modify material without applying any physical force.
- ▶ **On-Demand** - Produce everything you need in real time, without waiting for hard-tooling.

Uniquely Universal Features

▶ Universal Control Panel (UCP)

Our exclusive integrated materials database in the UCP print driver automatically determines the optimum processing settings for your target material. Just select the material type, enter the material thickness and press “start.”

▶ Rapid Reconfiguration™

Unique to ULS, Rapid Reconfiguration™ allows our modular platforms to be field-reconfigured with a variety of laser sources and other configurable components, in seconds. The most valuable component of a laser system, the laser source, is not tied to a particular machine, so almost any laser can be interchanged between different systems or exchanged with a laser of a different wattage to meet materials processing requirements.

▶ Laser Sources

Our patented, metal core, air-cooled, free-space slab, CO₂ lasers produce excellent beam quality with even power distribution, good near-field and far-field characteristics and long life. Dual lasers dramatically increase speed, edge quality and power.

▶ Dual Laser Configuration

Dual Laser Configuration allows the beams of two ULS laser sources to be combined into a single beam for maximum cutting, engraving and cutting power. This technology eliminates polarization effects and delivers beam quality that is superior to that of a single laser. Each laser can be controlled independently or combined to best suit material or application requirements.

▶ High Power Density Focusing Optics™

High Power Density Focusing Optics (HPDFO™) focuses the laser beam to the smallest spot size available, producing images with tighter tolerances, making even miniscule engraving details sharp.

▶ 1-Touch Laser Photo™

1-Touch Laser Photo is our popular software package that makes it quick and easy to reproduce stunning photographic images on nearly any material.

System Specifications

| PLS6.150D | |
|--|---|
| ▶ Work Surface Area (WxH) | 813 x 457 mm |
| ▶ Maximum Part Size¹ (WxHxD) | 940 x 584 x 229 mm |
| ▶ Dimensions (WxHxD) | 1118 x 991 x 914 mm |
| ▶ Rotary Capacity | Max. Diameter 203 mm |
| ▶ Motorized Z-Axis Lifting Capacity | 18 kg |
| ▶ Available Focus Lenses | 1.5 / 2.0 (Standard) / 2.5 / 4.0 / HPDFO™ |
| ▶ Laser Platform Interface Panel | Keypad and LCD display shows current file name, laser power, engraving speed, PPI and run time. |
| ▶ Operating System Compatibility | Requires a dedicated PC to operate. Compatible with Windows® XP/Vista/7/8/10 – 32/64 bit. |
| ▶ PC Connection | USB 2.0 or higher |
| ▶ Cabinet Style² | Floor-Standing |
| ▶ Laser Options | 10, 25, 30, 40, 50, 60, 75 W. Up to 150 W with dual lasers. |
| ▶ Approximate Weight | 156 kg |
| ▶ Power Requirements | 220V-240V/15A |
| ▶ Exhaust Connection | Two 102 mm ports 850 m ³ /hr at 1.5 kPa. |

USA

Global Headquarters

7845 E. Paradise Lane
Scottsdale, AZ 85260

+1 480-483-1214
moreinfo@ulsinc.com

Europe/Middle East/Africa

Lerchenfelder Gürtel 43
1160 Vienna, Austria

+43 1-402-22-50
eurosales@ulsinc.com

Japan

The Yokohama Landmark Tower
15th Fl. 2-2-1-1 Minato Mirai
Nishi-ku Yokohama-shi
Kanagawa-ken 220-8115 JAPAN

+81 45-224-2270
japansales@ulsinc.com

Distributed by:

CDRH Class 1 safety enclosure for CO₂ laser². Class 2 for red laser pointer.

¹ Maximum part size defined as used with 1.5 lens.

² CDRH Class 1 laser safety enclosure provides for safe operation without the need for an interlocked room or protective eyewear.



WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.

ULS laser systems are protected under one or more of U.S. Patents: 5,051,558; 5,661,746; 5,754,575; 5,867,517; 5,881,087; 5,894,493; 5,901,167; 5,982,803; 6,181,719; 6,313,433; 6,342,687; 6,423,925; 6,424,670; 6,983,001; 7,060,934; 7,415,051; 7,469,000; 7,715,454; 7,723,638; 7,947,919; 8,101,883; 8,294,062; 8,599,898; 8,603,217. Other U.S. and international patents pending. Made in the U.S.A.

©2015 Universal Laser Systems, Inc. All Rights Reserved. The Universal Laser Systems logo and name are registered trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

MC013-0715 REV2015.10_A4